

Package: MVPapp (via r-universe)

October 19, 2026

Title Interactive Platform for Pharmacometrics Model Visualization and Simulation

Version 1.0.0

Description An interactive 'shiny' application for exploring pharmacometrics models with minimal setup. Users can explore model structures, parameters and dosing regimens with 'mrgsolve', and compare simulations with observed data. Additional features include parameter sensitivity analysis, non-compartmental analysis (NCA), data exploration, variability assessment with virtual populations, and optional AI-assisted model translation. For design considerations of the app, see Choy et al. (2025) <[doi:10.1002/psp4.70023](https://doi.org/10.1002/psp4.70023)>.

License GPL (>= 3)

URL <https://github.com/stevechoy/MVPapp>,
<https://stevechoy.github.io/MVPapp/>

Encoding UTF-8

Roxygen list(markdown = TRUE)

Imports bslib (>= 0.5.1), cowplot, data.table (>= 1.14.2), dplyr (>= 1.1.0), DT, flextable (>= 0.6.10), ggplot2 (>= 3.4.4), grid, graphics, grDevices, htmltools (>= 0.5.5), magrittr, mrgsolve (>= 1.5.0), plotly (>= 4.10.1), rhandsontable (>= 0.3.8), rlang (>= 1.0.0), scales, shiny (>= 1.7.4.1), shinyAce, shinyBS (>= 0.61.1), shinycssloaders, shinydashboard (>= 0.7.2), shinyFiles, shinyjs (>= 1.0), shinythemes, shinyWidgets (>= 0.8.0), stats, stringr, tidyr, tools, utils, zip

Suggests curl, ellmer (>= 0.4.0), GGally, httr2, knitr, mime, ncar, NonCompartment, nonmem2mrgsolve, nonmem2rx, pdftools, rmarkdown, shinyalert, spelling, testthat (>= 3.0.0)

Additional_repositories <https://stevechoy.r-universe.dev>

Depends R (>= 4.1)

LazyData true

```
Collate ``utils-pipe.R" ``utils.R" ``ui_settings.R" ``code_templates.R"
``shiny_helpers.R" ``plot_helpers.R" ``data_utils.R"
``plots_data.R" ``simulation.R" ``variability.R" ``nca.R"
``sensitivity.R" ``llm.R" ``session_state.R" ``repro_bundle.R"
``run_mvp.R" ``zzz.R" ``data.R"
```

VignetteBuilder knitr

Config/testthat/edition 3

Language en-US

Config/roxygen2/version 8.0.0

Config/pak/sysreqs libcairo2-dev cmake libfontconfig1-dev libfreetype6-dev libfribidi-
dev make libharfbuzz-dev libicu-dev libjpeg-dev libpng-dev libtiff-dev libuv1-dev libwebp-
dev libxml2-dev libssl-dev zlib1g-dev

Repository https://stevechoy.r-universe.dev

Date/Publication 2026-10-18 23:58:50 UTC

RemoteUrl https://github.com/stevechoy/MVPapp

RemoteRef HEAD

RemoteSha 7961064fb161a78f0a65305cdde3003d77f7b30d

Contents

cdc.expand	2
nhanes.filtered	3
run_mvp	4
who.expand	9
Index	11

cdc.expand	<i>CDC pediatric virtual population</i>
------------	---

Description

A virtual pediatric population (birth to 20 years) simulated from the US Centers for Disease Control and Prevention (CDC) growth charts. Used by the app to sample age, weight and height when the "CDC" database is selected for variability simulations.

Usage

cdc.expand

Format

A data frame with 97,177 rows and 6 columns:

SEX Sex: 0 = male, 1 = female.

AGEMO Age (months).

AGEYR Age (years).

WT Body weight (kg).

HT Length/stature (cm).

BMI Body mass index (kg/m²).

Details

Body weight and stature were simulated from the published LMS parameters (Box-Cox power, median and coefficient of variation) of the weight-for-age and stature-for-age charts for each sex and month of age, by drawing standard normal Z-scores and applying $X = M(1 + LSZ)^{1/L}$. Rows with implausible BMI (outside 10 to 50 kg/m²) were removed. See `data-raw/databases.R` in the [GitHub repository](#) for the code.

Source

CDC growth charts, percentile data files with LMS values: https://www.cdc.gov/growthcharts/percentile_data_files.htm.

See Also

[nhanes.filtered](#), [who.expand](#)

nhanes.filtered	<i>NHANES population (1999-2023)</i>
-----------------	--------------------------------------

Description

Sex, age, body weight and height of participants in the US National Health and Nutrition Examination Survey (NHANES), cycles 1999-2000 to 2021-2023, aged 2 years and older. Used by the app to sample age, weight and height when the "NHANES" database is selected for variability simulations.

Usage

```
nhanes.filtered
```

Format

A data frame with 101,400 rows and 5 columns:

SEX Sex: 0 = male, 1 = female.

AGEMO Age (months), derived from AGEYR.

AGEYR Age (years).

WT Body weight (kg).

HT Standing height (cm).

Details

Demographics and body measures files were merged by participant and only complete records were kept. Age is recorded in whole years, so AGEMO is AGEYR * 12. See data-raw/databases.R in the [GitHub repository](#) for the code.

Source

Centers for Disease Control and Prevention (CDC), National Center for Health Statistics, National Health and Nutrition Examination Survey: <https://wwwn.cdc.gov/nchs/nhanes/Default.aspx>.

See Also

[cdc.expand](#), [who.expand](#)

run_mvp	<i>Launch Model Visualization Platform App</i>
---------	--

Description

run_mvp() launches the MVP app. mvp_app() returns the app as a Shiny app object without running it, e.g. for deployment on Posit Connect or shinyapps.io (an app.R containing MVPapp: :mvp_app() is sufficient).

The app is evaluated in its own environment (whose parent gives access to MVPapp and its key dependencies), so neither the global environment nor the search path is modified. Global options changed by the app are set when it starts and restored when it stops.

Usage

```
mvp_app(  
  appDir = system.file("shiny", package = "MVPapp"),  
  insert_watermark = TRUE,  
  max_dataset_size = 200,  
  authentication_code = NA_character_,  
  internal_version = TRUE,  
  pw_models_path = NA_character_,  
  llm_choices = c("Claude", "Gemini", "OpenAI", "OpenRouter", "OpenAI-Compatible"),
```

```

    "DeepSeek", "Azure OpenAI", "AWS Bedrock"),
  api_upload = NA_character_,
  api_chat = NA_character_,
  user_id = "MVP_user",
  reuse_context = FALSE,
  model_gemini = "gemini-3.8-flash",
  model_openai = "gpt-6.1-sol",
  model_anthropic = "claude-sonnet-5-5",
  model_openrouter = "arcee-ai/trinity-large-preview:free",
  model_openai_compatible = "gpt-5.2",
  model_deepseek = "deepseek-flash",
  model_apollo = "claude_4_6_sonnet",
  model_azure = "gpt-5.2",
  model_aws = "anthropic.claude-sonnet-5",
  temperature = 1,
  llm_seed = 42,
  model_lang = c("mrgsolve", "nonmem", "rxode2"),
  prompts_path = system.file("shiny/prompts.R", package = "MVPapp"),
  show_debugging_msg = FALSE,
  brand_color = NULL,
  brand_text_color = NULL,
  brand_logo = NULL,
  brand_favicon = NULL,
  page_title = NULL,
  ...
)

run_mvp(
  appDir = system.file("shiny", package = "MVPapp"),
  insert_watermark = TRUE,
  max_dataset_size = 200,
  authentication_code = NA_character_,
  internal_version = TRUE,
  pw_models_path = NA_character_,
  llm_choices = c("Claude", "Gemini", "OpenAI", "OpenRouter", "OpenAI-Compatible",
    "DeepSeek", "Azure OpenAI", "AWS Bedrock"),
  api_upload = NA_character_,
  api_chat = NA_character_,
  user_id = "MVP_user",
  reuse_context = FALSE,
  model_gemini = "gemini-3.8-flash",
  model_openai = "gpt-6.1-sol",
  model_anthropic = "claude-sonnet-5-5",
  model_openrouter = "arcee-ai/trinity-large-preview:free",
  model_openai_compatible = "gpt-5.2",
  model_deepseek = "deepseek-flash",
  model_apollo = "claude_4_6_sonnet",
  model_azure = "gpt-5.2",

```

```

model_aws = "anthropic.claude-sonnet-5",
temperature = 1,
llm_seed = 42,
model_lang = c("mrgsolve", "nonmem", "rxode2"),
prompts_path = system.file("shiny/prompts.R", package = "MVPapp"),
show_debugging_msg = FALSE,
brand_color = NULL,
brand_text_color = NULL,
brand_logo = NULL,
brand_favicon = NULL,
page_title = NULL,
...
)

```

Arguments

appDir	Character. Directory containing the app's app.R. Defaults to the copy installed with MVPapp and rarely needs changing.
insert_watermark	Logical. Default TRUE. Set to FALSE to remove the "For Internal Use Only" watermark from simulation plots and NCA reports.
max_dataset_size	Numeric. Default 200. Maximum upload dataset size in MB.
authentication_code	Character. Default NA_character_. Provide a string (e.g., password) to password-lock the entire app.
internal_version	Logical. Default TRUE. Set to FALSE when hosting the app on a server (e.g. AWS) where the working directory is not writable: NCA reports are then written to the session's temporary directory, and the help text for locked models points to GitHub instead. For internal deployments, it also selects the external Apollo endpoint.
pw_models_path	Character. Default NA_character_. Path to an R file defining password-gated models (see <code>system.file("shiny/passworded_models_example.R", package = "MVPapp")</code> and <code>vignette("supply-passwords")</code>).
llm_choices	Character vector of LLM providers offered in the app; the first one is selected by default. Defaults to all supported providers: "Claude", "Gemini", "OpenAI", "OpenRouter", "OpenAI-Compatible", "DeepSeek", "Azure OpenAI" and "AWS Bedrock". Internal-deployment providers (e.g. "PMx Co-Modeler", "Apollo") are also accepted.
api_upload	Character. Default NA_character_. API upload URL when using Dify-based workflows (internal deployment only)
api_chat	Character. Default NA_character_. Base URL required when using OpenAI-Compatible providers, e.g. "https://api.moonshot.ai/v1" ("/chat/completions" is appended automatically)
user_id	Character. Default MVP_user. User ID for LLMs

reuse_context	Logical. Default FALSE. Set to TRUE to re-use same conversation during retries.
model_gemini	Character. Default gemini-3.8-flash. Model for Gemini.
model_openai	Character. Default gpt-6.1-sol. Model for OpenAI / ChatGPT.
model_anthropic	Character. Default claude-sonnet-5-5. Model for Anthropic / Claude.
model_openrouter	Character. Default arcee-ai/trinity-large-preview:free. Model for OpenRouter.
model_openai_compatible	Character. Default gpt-5.2. Model for OpenAI-compatible providers.
model_deepseek	Character. Default deepseek-flash. Model for DeepSeek.
model_apollo	Character. Default claude_4_6_sonnet. Model for Apollo (internal deployment only).
model_azure	Character. Default gpt-5.2. Model for Azure OpenAI.
model_aws	Character. Default anthropic.claude-sonnet-5. Model for AWS Bedrock.
temperature	Numeric. Default 1. Between 0 (more deterministic) and 1 (more creative) (not all models support this).
llm_seed	Numeric. Default 42. Seed number for LLMs (not all models support this).
model_lang	Character. Default "mrgsolve" (the first element). Model translation language: "mrgsolve", "nonmem" (for testing only) or "rxode2" (for testing only).
prompts_path	Character. Path to an R file defining the LLM prompts. Defaults to the prompts installed with MVPapp. See vignette("automatic-translation") for more information.
show_debugging_msg	Logical. Default FALSE. Set to TRUE to output verbose working messages in the console, useful for debugging. AI translation responses are then also kept for review (see Details).
brand_color	Character. Default NULL (the default navy). A colour, e.g. "#F36633" or "orange", used for the navbar, active tab, box headers, table headers and loading spinners. See "Branding" in Details.
brand_text_color	Character. Default NULL. Colour of the text on brand_color (navbar and box headers). By default white or black is chosen for readability. Ignored if brand_color is NULL.
brand_logo	Character. Default NULL (no logo). Path to an image file (png, jpg, svg, ...) or a web URL, shown in the navbar in front of the page title.
brand_favicon	Character. Default NULL (the MVP icon shipped with the package). Path to an image file (png, ico, svg) or a web URL, used as the browser tab icon.
page_title	Character. Default NULL ("Model Visualization Platform (MVP)"). Title shown in the navbar. When set, it is also used as the browser tab title.
...	For run_mvp(), shiny::runApp() arguments (e.g. launch.browser, port). launch.browser defaults to TRUE here, so the app opens in your web browser (also from RStudio, which would otherwise use its viewer pane); use launch.browser = FALSE to turn that off. Any other named arguments are passed to the app.

Details

Objects kept for debugging. MVPapp does not write to the global environment. Objects useful for debugging are kept in an internal environment, `MVPapp:::mvp_state`, and remain available in the R session after the app is closed. List them with `ls(MVPapp:::mvp_state)`:

- `last_ev_df$model_1`, `last_ev_df$model_2`: the dosing event tables used in each model's most recent simulation (also used for the reproducible bundle download).
- `deps_env`: an internal cache used to run the app; not useful for debugging.
- With `show_debugging_msg = TRUE`, AI translation responses: `llm_result` (initial translation), `llm_refine` (latest retry that still failed), `llm_success` (Dify's reply when told the code compiled), `branch_model / branch_refine` (raw answers before cleaning) and `ellmer_chat_response / dify_chat_response` (raw chat responses).

Branding. For a company deployment, the title, colour, logo and favicon can be set when launching, without editing any package files. Each is optional; with all of them left at `NULL` the app looks as it always did.

```
run_mvp(brand_color = "#F36633",
        brand_logo   = "path/to/company_logo.png",
        brand_favicon = "path/to/favicon.png",
        page_title    = "Company Model Visualization Platform")
```

Image files are read from where they are and served by the app, so they do not need to be inside the package (a web URL also works). A logo with a transparent background and a height of about 30 pixels or more works best. `brand_color` replaces the navy in the navbar, the active tab, the headers and borders of the panels, the data table headers and the loading spinners. The same arguments work with `mvp_app()` for hosted deployments.

Hosting and security. MVPapp evaluates R and C++ model code supplied in the browser, so anyone who can open the app can run code on the server under the server account. `authentication_code` and the model passwords are a convenience to limit access to the interface and to hide models, not a security boundary: host the app only for trusted users, in a sandboxed account or container. The same applies to AI translation: its output is compiled automatically, and compiling `mrgsolve` code can itself run commands, so do not translate documents from untrusted sources on a shared server.

Without installing MVPapp (e.g. where package installation is restricted), the development version can also be launched from GitHub, provided its dependencies are installed: `shiny::runGitHub("MVPapp", "stevechoy", subdir = "inst/shiny")`.

Value

`run_mvp()` is called for its side effect of launching the app and returns the value of `shiny::runApp()` invisibly once the app is closed. `mvp_app()` returns a Shiny app object (class `shiny.appobj`).

See Also

<https://stevechoy.github.io/MVPapp/articles/supply-passwords.html> <https://stevechoy.github.io/MVPapp/articles/automatic-translation.html> [chat](#) for LLM chat interface.

Examples

```
if (interactive()) {
  run_mvp(insert_watermark = FALSE) # remove watermarks

  # Other examples:
  # run_mvp(launch.browser = FALSE) # do not open a browser (argument passed to runApp)
  # run_mvp(authentication_code = "some_password") # Password-lock the site,
  #                                           # could be useful in deployment
  # run_mvp(pw_models_path = "path/to/your/private/models.R") # see
  #   system.file("shiny/passworded_models_example.R", package = "MVPapp")
  # run_mvp(llm_choices = "Claude", model_anthropic = "claude-sonnet-5-5",
  #         temperature = 0) # Uses Claude only with reproducible results
}

# App object, e.g. as the only line of an app.R file for deployment:
app <- mvp_app(insert_watermark = FALSE)
```

who.expand

WHO pediatric virtual population

Description

A virtual pediatric population (birth to 10 years) simulated from the World Health Organization (WHO) Child Growth Standards and Growth Reference. Used by the app to sample age, weight and height when the "WHO" database is selected for variability simulations.

Usage

```
who.expand
```

Format

A data frame with 77,744 rows and 6 columns:

SEX Sex: 0 = male, 1 = female.

AGEMO Age (months).

AGEYR Age (years).

WT Body weight (kg).

HT Length/height (cm).

BMI Body mass index (kg/m²).

Details

Body weight and height were simulated from the published LMS parameters (Box-Cox power, median and coefficient of variation) for each sex and month of age, by drawing standard normal Z-scores and applying $X = M(1 + LSZ)^{1/L}$. Sources:

- Weight-for-age, 0 to 10 years.
- Length/height-for-age, 0 to 5 years (Child Growth Standards) and 5 to 10 years (Growth Reference 5-19 years).

Rows with implausible BMI (outside 10 to 50 kg/m²) were removed. See `data-raw/databases.R` in the [GitHub repository](#) for the code.

Source

WHO Child Growth Standards: <https://www.who.int/toolkits/child-growth-standards/standards/weight-for-age>, <https://www.who.int/toolkits/child-growth-standards/standards/length-height-for-age>. WHO Growth Reference 5-19 years: <https://www.who.int/toolkits/growth-reference-data-for-5to19-years/indicators/height-for-age>.

See Also

[cdc.expand](#), [nhanes.filtered](#)

Index

* **datasets**

- cdc.expand, [2](#)
- nhanes.filtered, [3](#)
- who.expand, [9](#)

cdc.expand, [2](#), [4](#), [10](#)
chat, [8](#)

mvp_app(run_mvp), [4](#)

nhanes.filtered, [3](#), [3](#), [10](#)

run_mvp, [4](#)

shiny::runApp(), [7](#), [8](#)

who.expand, [3](#), [4](#), [9](#)